



M-Bus

Universal bus for gauging probes and measuring instruments





SPC / XLS

Modbus
RS 232 / USB




Modbus
RS 232 / USB



Up to 2 inputs



Up to 99 inputs



Probes

Airgages

Scales / encoders

Instruments

Te



M-Bus



PLC


**PROFI[®]
BUS**

Modbus

RS 232 / USB

Modbus

Ethernet / USB



Controllers

Up to 61 inputs

Up to 254 inputs



Multiplexers

Temperature

Laser

Bluetooth

Force / position



Multiplexer modules

Item	Ref
MB-AG : 1 Air gage, compatible with any brand	MB-AG
MB-4i : 4 Metro inductive probes (ex. M802; M804P)	MB-4i
MB-4it : 4 Tesa-compatible inductive probes (ex. GT21)	MB-4it
MB-4im : 4 Mahr/Feinprüf inductive probes (ex. P2004M, 1318; 1300)	MB-4im
MB-8i : 8 Metro inductive probes (ex. M802; M804P)	MB-8i
MB-8it : 8 Tesa-compatible inductive probes (ex. GT21)	MB-8it
MB-2S : 2 Incremental probes or encoders with Heidenhain Pinout 11µA or 1Vss (DSUB15)	MB-2S
MB-2T : 2 Incremental probes or encoders with Heidenhain Pinout TTL (DSUB15)	MB-2T
MB-4M : 4 Magnescale (ex. Sony) probes (ex. DK812)	MB-4M
MB-4C : 4 Sylvac capacitive probes (ex P25)	MB-4C
MB-4D : 4 Digimatic instruments (conversion cables for other standards are available)	MB-4D
MB-8D : 8 Digimatic instruments (conversion cables for other standards are available)	MB-8D
MB-BT : 8 Sylvac or Bowers Bluetooth instruments	MB-BT
MB-1R : 1 RS232 device	MB-1R
MB-IO : 8 optocoupled Inputs/Outputs	MB-IO
MB-RL : 2 relay outputs and 6 inputs	MB-RL
MB-PS : Power supply for M-Bus	MB-PS
MB-FP : Force (Kistler piezo probe) VS Position (Resistive probe type Novotechnik or Gefran)	MB-FP
MB-µ33 : 1 input for SIP µ33 precision measuring bench	MB-µ33
MB-8µE : 8 laser probes from Micro Epsilon type optoNCDT 1320/1420	MB-8µE
MB-TP : 1 temperature sensor PT100 and 1 thermocouple type K	MB-TP

M-Bus Master modules

Item	Ref
MB-RS : RS-232 and USB communication (ASCII and modbus RTU) max 254 inputs	MB-RS
MB-IP : Ethernet and USB communication (ASCII and modbus TCP) max 254 inputs	MB-IP
MB-PB : Profibus DP module : max 61 inputs	MB-PB

M-Bus Master displays

Item	Ref
M1-M3 : Display with up to 2 inputs, M-Bus compatible. Refer to dedicated brochure	11040
M400 : Display with up to 99 M-Bus inputs. Refer to dedicated brochure	45500

M-Bus cables

Item	Ref
2m for M400 display and between modules	81210-2
5m for M400 display and between modules	81210-5
10m for M400 display and between modules	81210-10
1.5m for M1/M3 displays (with M8 connector)	81213-1.5



Metro
189 Rue de la Jonchère
74420 Boège
France
Phone. +33(0)4-50-39-08-49
Fax. +33(0)4-50-39-08-33
E-mail : info@metro-fr.com
Web : <http://www.metro-fr.com>

Your distributor

MBEN1000117

This document is not contractual and contains information corresponding to the level of technology at the date of printing. Metro reserves the right to modify and/or improve the product, whose characteristics are described in these documents, as required by new technology at any time. It is the purchaser's responsibility to inform himself, no matter what the circumstances, of the product's maintenance conditions and requirements. Metro reserves all rights, especially those arising from our "General Delivery Conditions".